


LÜFTER-SCHUTZGITTER




FGM- 40

Standard specification Many colors for option Easy for installation Notice: Weld Joints To Withstand 88 lbs pull force. Spacing between rigs to be equidistant 5.66 mm. Part meets 6.35 mm plug gauge test.
[more >](#)




FGM- 50

Standard specification Many colors for option Easy for installation Notice: Weld Joints To Withstand 88 lbs pull force. Spacing between rigs to be equidistant 4.33 mm. Part meets 6.35 mm plug gauge test.
[more >](#)




FGM- 60

Standard specification Many colors for option Easy for installation Notice: Weld Joints To Withstand 88 lbs pull force. Spacing between rigs to be equidistant 4.33 mm. Part meets 6.35 mm plug gauge test.




FGM- 80

Standard specification Many colors for option Easy for installation Notice: Weld Joints To Withstand 88 lbs pull force. Spacing between rigs to be equidistant 5.48 mm. Part meets 6.35 mm plug gauge test.
[more >](#)



FGM- 92

Standard specification Many colors for option Easy for installation [more >](#)



FGM-120

Standard specification Many colors for option Easy for installation Notice: Weld Joints To Withstand 88 lbs pull force. Spacing between rigs to be equidistant 5.66 mm. Part meets 6.35 mm plug gauge test.