

PRODUKT – PROGRAMM






METALLISIERTE FILM-KONDENSATOREN








SPECIFICATION: 0.5uF to 100uF of AC 250V to AC 600V



SPECIFICATION: 0.5uF to 25uF of AC 250V to AC 450V

					
Model	RA	RS	RB	BL	BX
Kapazitätsbereich in μF	10 – 200 μF	3 – 100 μF	3 – 100 μF	0.5 – 50 μF	0.5 – 50 μF
Kapazitätstoleranz in %	J (+/-5%); U (+/-5/10%) K (+/-10%);	5 – 10%	5 – 10%	5 – 10%	5 – 10%
Betriebsspannungsbereich in VAC	150 – 600 VAC	150 – 600 VAC	150 – 600 VAC	150 – 600 VAC	150 – 600 VAC
Temperaturbereich in $^{\circ}\text{C}$	- 25 bis + 70 $^{\circ}\text{C}$ - 40 bis + 85 $^{\circ}\text{C}$	- 25 bis + 70 $^{\circ}\text{C}$ - 40 bis + 85 $^{\circ}\text{C}$	- 25 bis + 70 $^{\circ}\text{C}$ - 40 bis + 85 $^{\circ}\text{C}$	- 25 bis + 70 $^{\circ}\text{C}$ - 40 bis + 85 $^{\circ}\text{C}$	- 25 bis + 70 $^{\circ}\text{C}$ - 40 bis + 85 $^{\circ}\text{C}$

					
Model	BK	BP	BW	AO	AB
Kapazitätsbereich in μF	2 – 50 μF	0.5 – 15 μF	0.5 – 20 μF	0.5 – 50 μF	0.5 – 50 μF
Kapazitätstoleranz in %	5 – 10%	5 – 10%	5 – 10%	5 – 10%	5 – 10%
Betriebsspannungsbereich in VAC	150 – 600 VAC	150 – 600 VAC	150 – 600 VAC	150 – 600 VAC	150 – 600 VAC
Temperaturbereich in $^{\circ}\text{C}$	- 25 bis + 70 $^{\circ}\text{C}$ - 40 bis + 85 $^{\circ}\text{C}$	- 25 bis + 70 $^{\circ}\text{C}$ - 40 bis + 85 $^{\circ}\text{C}$	- 25 bis + 70 $^{\circ}\text{C}$ - 40 bis + 85 $^{\circ}\text{C}$	- 25 bis + 70 $^{\circ}\text{C}$ - 40 bis + 85 $^{\circ}\text{C}$	- 25 bis + 70 $^{\circ}\text{C}$ - 40 bis + 85 $^{\circ}\text{C}$

S.Grad Components

Postfach 1763

D-82145 Planegg

Tel.: 089-85902187 Fax: 089-8595545 Email: info@grad-components.de www.grad-components.de